

No.

7430000

Version 1

1	Unique identification code of the product-type:	PROFI-DICHT-Abdichtung
2	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	batch number: see packaging of the product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Liquid applied roof waterproofing based on Polymethylmethacrylat (PMMA)
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	PROFI-DICHT-Abdichtung Icopal GmbH Capeller Straße 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	not relevant
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	not relevant
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard:	not relevant
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	German Institute for Construction Technology (DiBt) issued ETA-04/0004 on the basis of ETAG 005-04

9	Declared performance	<p>The product is used in waterproofing system PROFI-DICHT consisting of components:</p> <ul style="list-style-type: none"> • PROFI-DICHT-Abdichtung • PROFI-DICHT-Faserfix • PROFI-DICHT-Fläche • PROFI-DICHT-Grundierung • PROFI-DICHT-Grundierung F • PROFI-DICHT-Grundierung LF • PROFI-DICHT-Grundierung POCB • PROFI-DICHT-Markierung • PROFI-DICHT-Spachtel 	
	Essential properties	Performance	Harmonised technical specifications
	Working life	W3	ETAG 005 (3-2004)
	Climatic zones	M & S	
	Imposed loads	P1-P4	
	Roof slope	S1 – S4	
	Lowest surface temperature	TL4	
	Highest surface temperature	TH4	
	Resistance to spreading fire and radiant heat (EN 13501-5)	B _{ROOF} (t1), (t2), (t3)	
	Reaction to fire (EN 13501-1)	Class E	
	Water vapour diffusion resistance factor μ	10.000	
Resistance to wind loads	≥ 50 kPa		
10	<p>The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</p>		

Signed for and on behalf of the manufacturer by:

Werne, 26.06.2013 15.00 Uhr

Ort/Datum



Niels Graae, Geschäftsführer