



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7142805

Version 1

1	Unique identification Code of the product type	ALU-VILLATHERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen vapor barrier
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ALU-VILLATHERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	450 N/50 mm	
Tensile strength transverse	350 N/50 mm	
Elongation longitudinal	3 %	EN 13970:2004 /A1:2006
Elongation transverse	3 %	
resistance to static load method B	NPD	
resistance to static load method A	NPD	
resistance to tearing	100 N	
water vapour permability	< 0,02 g/m ² d	
durability: water vapour resistance after artificial ageing	< 0,02 g/m ² d	
shear resistance of joints	NPD	
Dangerous substances	Note 1&2	
flexibility at low temperatures (pliability)	- 6 °C	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7142815

Version 1

1	Unique identification Code of the product type	ALU-VILLATHERM K
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen vapor barrier
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ALU-VILLATHERM K ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	450 N/50 mm	
Tensile strength transverse	350 N/50 mm	
Elongation longitudinal	3 %	
Elongation transverse	3 %	
resistance to static load method B	NPD	
resistance to static load method A	NPD	
resistance to tearing	100 N	
water vapour permability	< 0,02 g/m ² d	
durability: water vapour resistance after artificial ageing	< 0,02 g/m ² d	
shear resistance of joints	NPD	
Dangerous substances	Note 1&2	
flexibility at low temperatures (pliability)	- 6 °C	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7112037

Version 1

1	Unique identification Code of the product type	Anschlussbahn bestreut
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Anschlussbahn bestreut ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	40 %	
Elongation transverse	40 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	NPD	
durability UV heat and water	NPD	
resistance to tearing	280 N	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013 10:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7105015

Version 1

1	Unique identification Code of the product type	Anschlussbahn unbestreut
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Anschlussbahn unbestreut ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN13707:2004/ A2:2009
Watertightness	200 kPa		
Tensile strength longitudinal	1050 N/50 mm		
Tensile strength transverse	1000 N/50 mm		
Elongation longitudinal	20 %		
Elongation transverse	20 %		
Root resistance	NPD		
resistance to static load method B	10 kg		
Resistance to impact method B	1250 mm		
durability UV heat and water	NPD		
resistance to tearing	300 N		
peel resistance of joints	NPD		
shear resistance of joints	1000 N		
durability: heat flow after heat oven exposure	NPD		
durability: flexibility at low temperatur after heat oven exposure	NPD		
flexibility at low temperatures (pliability)	- 28 °C		
Dangerous substances	Note 1&2		

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7122075

Version 1

1	Unique identification Code of the product type	BLITZ SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	BLITZ SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	100 kPa	
Tensile strength transverse	1000 N/50 mm	
Tensile strength longitudinal	1000 N/50 mm	
Elongation longitudinal	3 %	EN13707:2004/ A2:2009
Elongation transverse	3 %	
Root resistance	NPD	
resistance to static load method A	NPD	
Resistance to impact method B	NPD	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	NPD	
durability: flexibility at low temperatur after heat oven exposure	NPD	
flexibility at low temperatures (pliability)	- 25 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7111809

Version 1

1	Unique identification Code of the product type	ECO-ACTIV
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ECO-ACTIV ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	40 %	
Elongation transverse	40 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method A	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability UV heat and water	NPD	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

17.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7102600

Version 1

1	Unique identification Code of the product type	ECO-ACTIV-THERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ECO-ACTIV-THERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	40 %	
Elongation transverse	40 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	1800 mm	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	900 N	
durability: heat flow after heat oven exposure	110 °C	
flexibility at low temperatures (pliability)	-30 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013 12:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7118921

Version 1

1	Unique identification Code of the product type	ECO-ACTIV-THERM SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ECO-ACTIV-THERM SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1500 N/50 mm	
Tensile strength transverse	1500 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	2000 mm	
durability UV heat and water	NPD	
resistance to tearing	350 N	
peel resistance of joints	250 N	
shear resistance of joints	1450 N	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

27.06.2013 11:00
dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7201095

Version 1

1	Unique identification Code of the product type	ELASTO-VERAL
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ELASTO-VERAL ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0679 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0679-CPD-0122) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	NPD	
Reaction to fire	Class E	
Watertightness	NPD	
Tensile strength longitudinal	800 N/50 mm	
Tensile strength transverse	800 N/50 mm	
Elongation longitudinal	3 %	
Elongation transverse	3 %	
Root resistance	NPD	
resistance to static load method A	NPD	
Resistance to impact method B	NPD	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	+ 95 °C	
durability: flexibility at low temperatur after heat oven exposure	- 5 °C	
flexibility at low temperatures (pliability)	- 10 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Note: that classification is valid only for the tested built-up according TS 1187

Note: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

26.06.2013 14:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7102076

Version 1

1	Unique identification Code of the product type	ELASTOTHERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ELASTOTHERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	950 N/50 mm	
Tensile strength transverse	950 N/50 mm	
Elongation longitudinal	40 %	
Elongation transverse	40 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	1800 mm	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	900 N	
durability: heat flow after heat oven exposure	110 °C	
flexibility at low temperatures (pliability)	-30 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

24.06.2013 14:00
dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7112004

Version 1

1	Unique identification Code of the product type	EXPANDRIT-PLUS
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	EXPANDRIT-PLUS ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1000 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	NPD	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

17.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7192013

Version 1

1	Unique identification Code of the product type	GRÜNPLAST
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	GRÜNPLAST ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Tensile strength longitudinal	1050 N/50 mm	EN13707:2004/ A2:2009
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	nach FLL Richtl. geprüft	
resistance to static load method A	NPD	
Resistance to impact method B	1250 mm	
durability UV heat and water	NPD	
resistance to tearing	300 N	
peel resistance of joints	NPD	
shear resistance of joints	1000 N	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	NPD	
flexibility at low temperatures (pliability)	- 28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7192013B

Version 1

1	Unique identification Code of the product type	GRÜNPLAST (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	bitumen membrane for basement
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	GRÜNPLAST (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432 - CPD - 225212-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
watertightness at 60kPa	bestanden	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
resistance to static load method B	10 kg	
Resistance to impact method B	1250 mm	
resistance to tearing	300 N	
durability against artificial ageing/degradation: watertightness at 60kPa	bestanden	
durability against chemicals: watertightness at 2kPa	NPD	
durability against chemicals: watertightness at 60kPa	NPD	
shear resistance of joints	1000 N	
flexibility at low temperatures (pliability)	- 28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7191515

Version 1

1	Unique identification Code of the product type	GRÜNPLAST-TOP
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	GRÜNPLAST-TOP ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1500 N/50 mm	
Tensile strength transverse	1500 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	nach FLL Richtl. geprüft	
resistance to static load method A	20 kg	
Resistance to impact method B	2000 mm	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	1400 N	
durability: heat flow after heat oven exposure	105 °C	
durability: flexibility at low temperatur after heat oven exposure	NPD	
flexibility at low temperatures (pliability)	-28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

26.06.2013 16:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7498100

Version 1

1	Unique identification Code of the product type	MICORAL NB
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen vapor barrier
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	MICORAL NB ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 2007 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (2007-CPD-DS.4312-I/2013) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	200 N/50 mm	
Tensile strength transverse	200 N/50 mm	
Elongation transverse	25 %	
Elongation longitudinal	30 %	
resistance to static load method B	NPD	
resistance to static load method A	NPD	
resistance to tearing	NPD	
water vapour permability	< 0,01 g/m ² d	
durability: water vapour resistance after artificial ageing	< 0,01 g/m ² d	
shear resistance of joints	250 N	
Dangerous substances	Note 1&2	
flexibility at low temperatures (pliability)	- 20 °C	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7145050

Version 1

1	Unique identification Code of the product type	MICORAL SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen vapor barrier
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	MICORAL SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN 13970:2004 /A1:2006
Watertightness	200 kPa		
Tensile strength longitudinal	450 N/50 mm		
Tensile strength transverse	350 N/50 mm		
Elongation longitudinal	2 %		
Elongation transverse	2 %		
resistance to static load method B	NPD		
resistance to static load method A	NPD		
resistance to tearing	100 N		
water vapour permability	< 0,01 g/m ² d		
durability: water vapour resistance after artificial ageing	< 0,01 g/m ² d		
shear resistance of joints	NPD		
Dangerous substances	Note 1&2		
flexibility at low temperatures (pliability)	- 20 °C		

Note 1: This product does not contain asbestos or tar constituents
 Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

Werne _____ 28.06.2013
 dd/mm/yyyy



 Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7142835

Version 1

1	Unique identification Code of the product type	MICOTHERM SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen vapor barrier
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	MICOTHERM SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	450 N/50 mm	
Tensile strength transverse	350 N/50 mm	
Elongation longitudinal	3 %	EN 13970:2004 /A1:2006
Elongation transverse	3 %	
resistance to static load method B	NPD	
resistance to static load method A	NPD	
resistance to tearing	100 N	
water vapour permability	< 0,01 g/m ² d	
durability: water vapour resistance after artificial ageing	< 0,01 g/m ² d	
shear resistance of joints	NPD	
Dangerous substances	Note 1&2	
flexibility at low temperatures (pliability)	- 6 °C	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

Werne 28.06.2013
dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7201194

Version 1

1	Unique identification Code of the product type	MISTRAL C
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	MISTRAL C ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0679 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0679-CPD-0122) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	NPD	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	800 N/50 mm	
Tensile strength transverse	550 N/50 mm	
Elongation longitudinal	40 %	
Elongation transverse	40 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	1250 mm	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	600 N	
durability: heat flow after heat oven exposure	+ 95 °C	
durability: flexibility at low temperatur after heat oven exposure	- 10 °C	
flexibility at low temperatures (pliability)	- 14 °C	
Dangerous substances	Note 1&2	

EN13707:2004/
A2:2009

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne 25.06.2013 14:00
 dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7113055

Version 1

1	Unique identification Code of the product type	MONOFUTUR
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	MONOFUTUR ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1500 N/50 mm	
Tensile strength transverse	1500 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	2000 mm	
durability UV heat and water	NPD	
resistance to tearing	350 N	
peel resistance of joints	250 N	
shear resistance of joints	1400 N	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

27.06.2013 14:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7118043

Version 1

1	Unique identification Code of the product type	MONOTHERM SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	MONOTHERM SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1500 N/50 mm	
Tensile strength transverse	1500 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	2000 mm	
durability UV heat and water	NPD	
resistance to tearing	350 N	
peel resistance of joints	250 N	
shear resistance of joints	1400 N	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne 26.06.2013 16:00
dd/mm/yyyy


Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7105007

Version 1

1	Unique identification Code of the product type	POLAR
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLAR ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN13707:2004/ A2:2009
Watertightness	200 kPa		
Tensile strength longitudinal	1050 N/50 mm		
Tensile strength transverse	1000 N/50 mm		
Elongation longitudinal	20 %		
Elongation transverse	20 %		
Root resistance	NPD		
resistance to static load method A	NPD		
Resistance to impact method B	1250 mm		
durability UV heat and water	NPD		
resistance to tearing	300 N		
peel resistance of joints	NPD		
shear resistance of joints	NPD		
durability: heat flow after heat oven exposure	110 °C		
durability: flexibility at low temperatur after heat oven exposure	NPD		
flexibility at low temperatures (pliability)	- 28 °C		
Dangerous substances	Note 1&2		

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7105007B

Version 1

1	Unique identification Code of the product type	POLAR (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	bitumen membrane for basement
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLAR (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432 - CPD - 225212-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
watertightness at 60kPa	bestanden	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
resistance to static load method B	10 kg	
Resistance to impact method B	1250 mm	
resistance to tearing	300 N	
durability against artificial ageing/degradation: watertightness at 60kPa	bestanden	
durability against chemicals: watertightness at 2kPa	NPD	
durability against chemicals: watertightness at 60kPa	NPD	
shear resistance of joints	1000 N	
flexibility at low temperatures (pliability)	- 28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7122051

Version 1

1	Unique identification Code of the product type	POLAR SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLAR SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0958 - CPD - DK041) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN13707:2004/ A2:2009
Watertightness	200 kPa		
Tensile strength longitudinal	1050 N/50 mm		
Tensile strength transverse	1000 N/50 mm		
Elongation longitudinal	20 %		
Elongation transverse	20 %		
Root resistance	NPD		
resistance to static load method A	NPD		
Resistance to impact method B	1250 mm		
durability UV heat and water	NPD		
resistance to tearing	300 N		
peel resistance of joints	NPD		
shear resistance of joints	1000 N		
durability: heat flow after heat oven exposure	110 °C		
durability: flexibility at low temperatur after heat oven exposure	NPD		
flexibility at low temperatures (pliability)	- 30 °C		
Dangerous substances	Note 1&2		

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7122051B

Version 1

1	Unique identification Code of the product type	POLAR SK (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	bitumen membrane for basement
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLAR SK (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432 - CPD - 225212-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
watertightness at 60kPa	bestanden	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
resistance to static load method B	10 kg	
Resistance to impact method B	1250 mm	
resistance to tearing	300 N	
durability against artificial ageing/degradation: watertightness at 60kPa	bestanden	
durability against chemicals: watertightness at 2kPa	NPD	
durability against chemicals: watertightness at 60kPa	NPD	
shear resistance of joints	1000 N	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7107305

Version 1

1	Unique identification Code of the product type	POLAR-TOP
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLAR-TOP ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	NPD	
resistance to static load method A	10 kg	
Resistance to impact method B	NPD	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	NPD	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013 10:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7191950

Version 1

1	Unique identification Code of the product type	POLAR-TOP WS
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLAR-TOP WS ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	nach FLL Richtl. geprüft	
resistance to static load method A	10 kg	
Resistance to impact method B	NPD	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	NPD	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Note: that classification is valid only for the tested built-up according TS 1187

Note: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013 10:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7116810

Version 1

1	Unique identification Code of the product type	POLARTHERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLARTHERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN13707:2004/ A2:2009
Watertightness	200 kPa		
Tensile strength longitudinal	1050 N/50 mm		
Tensile strength transverse	1000 N/50 mm		
Elongation longitudinal	20 %		
Elongation transverse	20 %		
Root resistance	NPD		
resistance to static load method A	NPD		
Resistance to impact method B	1250 mm		
durability UV heat and water	NPD		
resistance to tearing	300 N		
peel resistance of joints	NPD		
shear resistance of joints	NPD		
durability: heat flow after heat oven exposure	110 °C		
durability: flexibility at low temperatur after heat oven exposure	NPD		
flexibility at low temperatures (pliability)	- 28 °C		
Dangerous substances	Note 1&2		

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7117810

Version 1

1	Unique identification Code of the product type	POLARTHERM SK
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLARTHERM SK ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN13707:2004/ A2:2009
Watertightness	200 kPa		
Tensile strength longitudinal	1050 N/50 mm		
Tensile strength transverse	1000 N/50 mm		
Elongation longitudinal	20 %		
Elongation transverse	20 %		
Root resistance	NPD		
resistance to static load method A	NPD		
Resistance to impact method B	1250 mm		
durability UV heat and water	NPD		
resistance to tearing	300 N		
peel resistance of joints	NPD		
shear resistance of joints	NPD		
durability: heat flow after heat oven exposure	110 °C		
durability: flexibility at low temperatur after heat oven exposure	NPD		
flexibility at low temperatures (pliability)	- 28 °C		
Dangerous substances	Note 1&2		

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7117810B

Version 1

1	Unique identification Code of the product type	POLARTHERM SK (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	bitumen membrane for basement
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	POLARTHERM SK (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432 - CPD - 225212-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
watertightness at 60kPa	bestanden	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
resistance to static load method B	10 kg	
Resistance to impact method B	1250 mm	
resistance to tearing	300 N	
durability against artificial ageing/degradation: watertightness at 60kPa	bestanden	
durability against chemicals: watertightness at 2kPa	NPD	
durability against chemicals: watertightness at 60kPa	NPD	
shear resistance of joints	1000 N	
flexibility at low temperatures (pliability)	- 28 °C	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7193003

Version 1

1	Unique identification Code of the product type	SCR-Matte
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	SCR-Matte ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7113600

Version 1

1	Unique identification Code of the product type	SICO-TOP
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	SICO-TOP ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1500 N/50 mm	
Tensile strength transverse	1500 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	2000 mm	
durability UV heat and water	NPD	
resistance to tearing	350 N	
peel resistance of joints	250 N	
shear resistance of joints	1400 N	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013 14:15

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7131707

Version 1

1	Unique identification Code of the product type	SICOTEC
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	SICOTEC ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1400 N/50 mm	
Tensile strength transverse	1400 N/50 mm	
Elongation longitudinal	3 %	
Elongation transverse	3 %	
resistance to static load method B	NPD	
Root resistance	NPD	
resistance to static load method A	NPD	
resistance to tearing	350 N	
water vapour permability	< 0,06 g/m ² d	
durability: water vapour resistance after artificial ageing	< 0,06 g/m ² d	
durability UV heat and water	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	NPD	
durability: heat flow after heat oven exposure	NPD	
durability: flexibility at low temperatur after heat oven exposure	NPD	
flexibility at low temperatures (pliability)	- 28 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7134900

Version 1

1	Unique identification Code of the product type	SICOTHERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen vapor barrier
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	SICOTHERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1400 N/50 mm	
Tensile strength transverse	1400 N/50 mm	
Elongation longitudinal	3 %	
Elongation transverse	3 %	
resistance to static load method B	NPD	
resistance to static load method A	NPD	
resistance to tearing	350 N	
water vapour permability	< 0,06 g/m ² d	
durability: water vapour resistance after artificial ageing	< 0,06 g/m ² d	
shear resistance of joints	NPD	
Dangerous substances	Note 1&2	
flexibility at low temperatures (pliability)	- 6 °C	

Note 1: This product does not contain asbestos or tar constituents
 Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

Werne 28.06.2013
 dd/mm/yyyy

i. A. L. Rehn
 Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7550004

Version 1

1	Unique identification Code of the product type	TERANAP JS
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	TERANAP JS ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0679 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0679-CPD-0122) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	700 N/50 mm	
Tensile strength transverse	500 N/50 mm	
Elongation longitudinal	40 %	
Elongation transverse	40 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	2000 mm	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	250 N	
shear resistance of joints	600 N	
durability: heat flow after heat oven exposure	+ 100 °C	
durability: flexibility at low temperatur after heat oven exposure	- 10 °C	
flexibility at low temperatures (pliability)	- 15 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

17.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7103923

Version 1

1	Unique identification Code of the product type	THERMOSOLO
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	THERMOSOLO ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	850 N/50 mm	
Tensile strength transverse	800 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	NPD	
resistance to static load method A	15 kg	
Resistance to impact method B	1.250 mm	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	800 N	
durability: heat flow after heat oven exposure	105 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

17.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7220135

Version 1

1	Unique identification Code of the product type	UNIVERSAL
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Plastic and rubber sheet for roof waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	UNIVERSAL ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0620 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0620-CPD-74182) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	EN 13956:2012
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1185 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
resistance to static load method B	20 kg	
Resistance to impact method A	1250 mm	
Resistance to impact method B	1250 mm	
durability UV heat and water: 1000 h UV	Pass	
durability UV heat and water	Pass	
resistance to tearing longitudinal	400 N	
resistance to tearing transverse	400 N	
peel resistance of joints	80 N	
shear resistance of joints	800 N	
foldability at low temperature	- 25 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Note: that classification is valid only for the tested built-up according TS 1187

Note: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

06.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7220135B

Version 1

1	Unique identification Code of the product type	UNIVERSAL (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Plastic and rubber damp proof sheet including basement tanking: type T
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	UNIVERSAL (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0620 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0620-CPD-74181) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 13967:2012
Tensile strength longitudinal	1185 N/50 mm	
Elongation longitudinal	20 %	
Tensile strength transverse	1000 N/50 mm	
Elongation transverse	20 %	
resistance to static load method B	20 kg	
Resistance to impact method A	1250 mm	
Resistance to impact method B	1250 mm	
resistance to tearing	400 N	
shear resistance of joints	800 N	
durability against artificial ageing/degradation: watertightness at 2kPa	Pass	
durability against artificial ageing/degradation: watertightness at 60kPa	Pass	
durability against artificial ageing/degradation: watertightness at 2kPa	Pass	
durability against artificial ageing/degradation: watertightness at 60kPa	Pass	
durability against chemicals: watertightness at 2kPa	Pass	
durability against chemicals: watertightness at 60kPa	Pass	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

30/07/2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7220130

Version 1

1	Unique identification Code of the product type	UNIVERSAL SA
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Plastic and rubber sheet for roof waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	UNIVERSAL SA ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0620 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0620-CPD-74182) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	EN 13956:2012
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1185 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
resistance to static load method B	20 kg	
Resistance to impact method A	1250 mm	
Resistance to impact method B	1250 mm	
resistance to tearing longitudinal	400 N	
resistance to tearing transverse	400 N	
peel resistance of joints	80 N	
shear resistance of joints	800 N	
durability UV heat and water: 1000 h UV		
foldability at low temperature	- 25 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Note: that classification is valid only for the tested built-up according TS 1187

Note: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

27.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7220140

Version 1

1	Unique identification Code of the product type	UNIVERSAL WS
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Plastic and rubber sheet for roof waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	UNIVERSAL WS ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0620 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0620-CPD-74182) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	EN 13956:2012
Reaction to fire	Class E	
Watertightness	400 kPa	
Tensile strength longitudinal	1185 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	20 %	
Elongation transverse	20 %	
Root resistance	Pass	
resistance to static load method A	20 kg	
resistance to static load method B	20 kg	
Resistance to impact method A	1250 mm	
Resistance to impact method B	1250 mm	
resistance to tearing longitudinal	400 N	
resistance to tearing transverse	400 N	
peel resistance of joints	80 N	
shear resistance of joints	800 N	
durability UV heat and water: 1000 h UV	Pass	
foldability at low temperature	- 25 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Note: that classification is valid only for the tested built-up according TS 1187

Note: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7220140B

Version 1

1	Unique identification Code of the product type	UNIVERSAL WS (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Plastic and rubber damp proof sheet including basement tanking: type T
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	UNIVERSAL WS (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0620 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0620-CPD-74181) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 13967:2012
Tensile strength longitudinal	1185 N/50 mm	
Elongation longitudinal	20 %	
Tensile strength transverse	1000 N/50 mm	
Elongation transverse	20 %	
resistance to static load method B	20 kg	
Resistance to impact method A	1250 mm	
Resistance to impact method B	1250 mm	
resistance to tearing	400 N	
shear resistance of joints	800 N	
watertightness at 2kPa	Pass	
watertightness at 60kPa	Pass	
durability against artificial ageing/degradation: watertightness at 2kPa	Pass	
durability against artificial ageing/degradation: watertightness at 60kPa	Pass	
durability against chemicals: watertightness at 2kPa	Pass	
durability against chemicals: watertightness at 60kPa	bestanden	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7134830

Version 1

1	Unique identification Code of the product type	VENTITHERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	VENTITHERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7113250

Version 1

1	Unique identification Code of the product type	VENTURA
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	VENTURA ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B roof (t1)	
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1500 N/50 mm	
Tensile strength transverse	1500 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	NPD	
resistance to static load method A	20 kg	
Resistance to impact method B	NPD	
Resistance to impact method A	NPD	
durability UV heat and water	NPD	
resistance to tearing	NPD	
peel resistance of joints	NPD	
shear resistance of joints	NPD	
durability: heat flow after heat oven exposure	110 °C	
durability: flexibility at low temperatur after heat oven exposure	-26 °C	
flexibility at low temperatures (pliability)	- 30 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

26.06.2013 16:00

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7131052

Version 1

1	Unique identification Code of the product type	VILLADRIT
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	VILLADRIT ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
Root resistance	NPD	
resistance to static load method A	NPD	
Resistance to impact method B	1250 mm	
durability UV heat and water	NPD	
resistance to tearing	300 N	
peel resistance of joints	NPD	
shear resistance of joints	1000 N	
durability: heat flow after heat oven exposure	NPD	
durability: flexibility at low temperatur after heat oven exposure	NPD	
flexibility at low temperatures (pliability)	- 20 °C	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne 28.06.2013
dd/mm/yyyy


Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7131052B

Version 1

1	Unique identification Code of the product type	VILLADRIT (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	bitumen membrane for basement
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	VILLADRIT (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432 - CPD - 225212-2) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
watertightness at 60kPa	bestanden	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
resistance to static load method B	10 kg	
Resistance to impact method B	1250 mm	
resistance to tearing	300 N	
durability against artificial ageing/degradation: watertightness at 60kPa	bestanden	
durability against chemicals: watertightness at 2kPa	NPD	
durability against chemicals: watertightness at 60kPa	NPD	
shear resistance of joints	1000 N	
flexibility at low temperatures (pliability)	- 20 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7132810

Version 1

1	Unique identification Code of the product type	VILLATHERM
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Bitumen membrane for waterproofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	VILLATHERM ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432- CPD - 224518-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class E		EN13707:2004/ A2:2009
Watertightness	200 kPa		
Tensile strength longitudinal	1050 N/50 mm		
Tensile strength transverse	1000 N/50 mm		
Elongation longitudinal	4 %		
Elongation transverse	4 %		
Root resistance	NPD		
resistance to static load method A	NPD		
Resistance to impact method B	1250 mm		
durability UV heat and water	NPD		
resistance to tearing	300 N		
peel resistance of joints	NPD		
shear resistance of joints	1000 N		
durability: heat flow after heat oven exposure	NPD		
durability: flexibility at low temperatur after heat oven exposure	NPD		
flexibility at low temperatures (pliability)	- 14 °C		
Dangerous substances	Note 1&2		

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed



DECLARATION OF PERFORMANCE
In accordance with Regulation (EU) N° 305/2011

No

7132810B

Version 1

1	Unique identification Code of the product type	VILLATHERM (Bauwerksabdichtung)
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 01.07.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	bitumen membrane for basement
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	VILLATHERM (Bauwerksabdichtung) ICOPAL GmbH Capeller Strasse 150 59368 Werne Germany
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified factory production control certification body Bodycompany No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. (0432 - CPD - 225212-1) () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	
Watertightness	200 kPa	
watertightness at 60kPa	bestanden	
Tensile strength longitudinal	1050 N/50 mm	
Tensile strength transverse	1000 N/50 mm	
Elongation longitudinal	4 %	
Elongation transverse	4 %	
resistance to static load method B	10 kg	
Resistance to impact method B	1250 mm	
resistance to tearing	300 N	
durability against artificial ageing/degradation: watertightness at 60kPa	bestanden	
durability against chemicals: watertightness at 2kPa	NPD	
durability against chemicals: watertightness at 60kPa	NPD	
shear resistance of joints	1000 N	
flexibility at low temperatures (pliability)	- 14 °C	
Dangerous substances	Note 1&2	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Werne

28.06.2013

dd/mm/yyyy



Signed